



- Type 2
- Power supply system: TN 1+0 configuration
- $U_C = 440 \text{ V}$
- $I_{\text{max}} = 40 \text{ kA}$
- Horizontal pitch: 1 Div.
- With remote signalling contact
- Modular design
- Mounting on 35 mm DIN rail

## Technical Specifications

Nominal voltage	$U_N$
Maximum operating voltage	$U_C$
Nominal discharge current (8/20 $\mu\text{s}$ )	$I_n$
Maximum discharge current (8/20 $\mu\text{s}$ )	$I_{\text{max}}$
Voltage protection level	$U_p$
Short-circuit current rating	$I_{\text{SCCR}}$
Maximum overcurrent protection	
TOV behavior	$U_T$
Response time	$t_A$
Cross-section of connected conductors rigid	
Cross-section of connected conductors flexible	
Fault indication	
Remote signalling contact	
Remote contacts ratings	
Remote contacts cross-section	
Degree of protection	
Operating temperature	
Permissible relative humidity	RH
Mounting on	
According to standard	

## FE T2 440 40 FM

400 V AC
440 V AC
20 kA
40 kA
< 1.9 kV
25 kA
125 A gG
580 V (5 s / withstand mode)
25 ns
1 mm <sup>2</sup> ... 35 mm <sup>2</sup>
1 mm <sup>2</sup> ... 25 mm <sup>2</sup>
yes
potential free changeover contact
250 V/0.5 A AC; 250 V/0.1 A DC
1.5 mm <sup>2</sup>
IP 20
-40 °C ... +80 °C
5% ... 95%
35 mm DIN rail
EN 61643-11:2012 / IEC 61643-11:2011 / T2

## Order Information

Order number	206 121
Gross weight / net weight	152 g / 128 g
Package dimensions L x W x H	124 x 80 x 24 mm
Customs tariff number	85363030

