



- Type 1+2
- Power supply system: TT 3+1 configuration / TNS 4+0 configuration
- $I_{imp} / \text{Pole} = 25 \text{ kA}$
- No leakage current
- No follow current
- Horizontal pitch: 8 Div.
- Available with remote signalling contact
- Modular design
- Mounting on 35 mm DIN rail

Technical Specifications

Nominal voltage	U_N
Maximum operating voltage L-N / N-PE	U_C
Nominal load current (V-type through wiring)	I_L
Lightning impulse current (10/350 μs) L-N / N-PE	I_{imp}
Total discharge current (10/350 μs)	I_{total}
Nominal discharge current (8/20 μs) L-N / N-PE	I_n
Maximum discharge current (8/20 μs) L-N / N-PE	I_{max}
Voltage protection level	U_p
Follow current extinguishing capability N-PE	I_n
Short-circuit current rating	I_{SCCR}
Maximum overcurrent protection / with V-type through wiring	
TOV behavior L-N	U_T
TOV behavior L-N	U_T
TOV behavior N-PE	U_T
Response time	t_A
Cross-section of connected conductors rigid	
Cross-section of connected conductors flexible	
Fault indication L-N	
Degree of protection	
Operating temperature	
Permissible relative humidity	RH
Mounting on	
According to standard	

FE T1+T2 260 TT 25

230 V AC / 400 V AC
260 V AC / 255 V AC
125 A
25 kA / 100 kA
100 kA
30 kA / 100 kA
60 kA / 100 kA
< 1.5 kV
100 A
50 kA
250 A gG / 125 A gG
335 V (5 s / withstand mode)
440 V (120 min / withstand mode)
1200 V (200 ms / withstand mode)
100 ns
2.5 mm ² ... 50 mm ²
2.5 mm ² ... 35 mm ²
yes
IP 20
-40 °C ... +80 °C
5% ... 95%
35 mm DIN rail
EN 61643-11:2012 / IEC 61643-11:2011 / T1, T2

Order Information

Order number	504 720
Gross weight / net weight	1282 g / 1222 g
Package dimensions L x W x H	158 x 104 x 84 mm
Customs tariff number	85363090

504 720
1282 g / 1222 g
158 x 104 x 84 mm
85363090

