



Surge arrester for protection of telecommunications and signaling system against surge voltage

- Type C2, C3
- $I_{total} (8/20 \mu s) = 10 \text{ kA}$
- Mounting on LSA disconnection rail

Technical Specifications

Maximum operating voltage	U_C
Nominal load current	I_L
C2 nominal discharge current (8/20 μs) per core	I_n
C2 total discharge current (8/20 μs) cores-PE	I_{total}
C2 voltage protection level mode core-core at I_n	U_p
C2 voltage protection level mode core-PE at I_n	U_p
C3 voltage protection level mode core-core at 1 kV/ μs	U_p
C3 voltage protection level mode core-PE at 1 kV/ μs	U_p
Response time core-core / core-PE	t_A
Serial resistance per core	R
Threshold frequency core-core	f
Connection / mounting	
Accessories	
Degree of protection	
Operating temperature	
Permissible relative humidity	RH
According to standard	

Order Information

Order number	
Gross weight / net weight	
Customs tariff number	

FED LSA ISDN

85 V AC / 120 V DC
0.5 A
5 kA
10 kA
220 V
400 V
170 V
350 V
1 ns / 100 ns
1.6 Ω
16 MHz
LSA disconnection rail
Grounding rail
IP 20
-40 °C ... +70 °C
5% ... 95%
EN 61643-21+A1, A2:2013 / IEC 61643-21+A1, A2:2012, C2, C3

605 160
12 g / 4 g
85363010

